



Features

- Industrial-grade 10.1" WXGA LCD panel with 30k backlight lifetime
- True-flat touchscreen with multi-touch projected capacitive control
- Stainless Steel Front Panel, Front IP66 Waterproof
- Intel® Celeron® J1900 quad-core 2.0 GHz processor
- 1 x DDR3 SDRAM, max.8GB, 1 x mSATA / 1 x 2.5" SATA SSD
- 2 x Intel® 211 1GbE Ethernet, support WoL and PXE
- 2 x RS232/422/485, RS485 support automatic flow control
- Support TPM2.0 hardware security
- Supports embedded / VESA 100mm x 100mm mounting holes
- 9V to 36V DC Wide Range Power Input, Supporting OVP / OCP / RPP

Specifications

System	
CPU	Intel® Bay Trail Celeron J1900 Quad-core 2.0GHz, TDP 10W
L2 Cache	2MB
System Chipset	Integrated with Intel® SoC
Memory	DDR3L 1333MHz 4GB, Up to 8GB
Harddisk	1 x mSATA 128G SSD (250G / 500G / 1TB SSD) / 1 x 2.5" SATA
Graphics	Intel HD Graphics
Network	Intel® I211-AT GbE LAN
Audio	Realtek ACL662 Audio controller
TPM	TPM 2.0
Watchdog Timer	Software Programmable Supports 1~255 sec. System Reset
Operation System	Windows 7 / 8 / 10, Linux, Ubuntu
I / O	
VIDEO	1 x H-DMI
Ethernet	2 x LAN (10/100/1000 Mbps)
USB	3 x USB2.0 / 1 x USB3.0
COM	2 x RS-232 / 422 / 485 (Adjustable through BIOS)
Audio	1x Audio_out & Mic_in
Wireless Network	Optional (WiFi / Bluetooth / 4G)
Expansion	
M.2	1*M.2 (Key-E, 2230, PCIe+USB, Wifi+BT)
	1*M.2 (Key-B, 3042, USB2.0, 4G)
	1*mSATA SSD
SIM Socket	1x SIM Socket
Display	
LCD Size	10.1" (16:10)
Resolution	1280 x 800
Brightness (cd/m ²)	400 cd/m ²
Contrast Ratio	900:1
Backlight MTBF	30000 Hr Hr (min.)
Viewing Angle	85 / 85 / 85 / 85 (CR≥10) (L / R / U / D)
Touch screen	
Touch Type	10 point PCAP
Surface Hardness	≥7H

Power	
Power Adapter	1 x Optional AC/DC 12V/5A , 60W
Power Mode	Support AT, ATX Mode
Power Input	2-pin Terminal Block Connector with Power Input 9~36VDC
Power Protection	OVP (Over Voltage Protection) OCP (Over Current Protection) RPP (Reverse Polarity Protection)
Power Consumption	≤30W
Physical	
Material	SUS 304 Panel + SECC
Mounting	Stand / Wall / VESA / Panel
Dimension (W x H x D)	275 x 194 x 58 mm
Cut-out Size	263 x 182 mm
Packing Size	360 x 180 x 320 mm
Weight (Net)	2.5 KG
Environment	
Operating Temperature	-20~70°C (-4~158°F)
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	Front Panel IP66
EMC	CE, FCC, UL, KC, Class A, ROHS , IEC / EN 62368-1

Dimension & I/O

I / O Definition:

A. DC 9V~36V	B. COM1:RS-232 / 422 / 485
C. COM2:RS-232 / 422 / 485	D. 2 x LAN
E. H-DMI	F. 1 x USB 3.0 / 1 x USB 2.0
G. 2 x USB 2.0	H. Audio
I. Extension Switch	J. Power Button

Panel Cutout Dimensions: 263 x 182 mm (10.35 x7.16 in)

Ordering info

Available models	Description
PPC-J010WCC	10.1" Fanless Industrial Panel PC Intel® Bay Trail Celeron J1900 2.0GHz Processor With Capcice touch

Packing list

1 x Standard product
1 x Utility DVD Driver
1 x 60W PSU (Power Supply)
1 x Power cable & plug
8 x Panel mount metal clips