



## Features

- Industrial-grade 13.3" FHD LCD panel with 50k backlight lifetime
- True-flat touchscreen with multi-touch projected capacitive control
- IP66 grade aluminum alloy front panel
- Intel® Celeron® J6412 quad-core 2.0 GHz processor
- 1 x DDR4 SDRAM, max.32GB, 1 x M.2 2280 / 1 x 2.5" SATA SSD
- 3 x Intel® 226-V 2.5GbE Ethernet, support WoL and PXE
- 2 x RS232/422/485, RS485 support automatic flow control
- Support TPM2.0 hardware security
- Supports embedded / VESA 100mm x 100mm mounting holes
- 9V to 36V DC Wide Range Power Input, Supporting OVP / OCP / RPP

## Specifications

System	
CPU	Intel® Elkhart Lake Celeron J6412 Quad-core 2.0GHz , TDP 10W
L2 Cache	1.5MB
System Chipset	Integrated with Intel® SoC
Memory	1 x DDR4L 3200MHz 4GB, MAX 32GB
Harddisk	1 x M.2 120G SSD ( 250G / 500G / 2TB SSD) / 1 x 2.5" SATA
Graphics	Intel® UHD Graphics for 10th Gen Intel® Processors
Network	Intel® 226-V GbE LAN
Audio	Realtek ACL897 Audio controller
TPM	TPM 2.0
Watchdog Timer	Software Programmable Supports 1~255 sec. System Reset
Operation System	Windows 10 / 11, Linux, Ubuntu
I/O	
VIDEO	1 x H-DMI
Ethernet	3 x LAN (10/100/1000/2500 Mbps)
USB	4 x USB 3.0
COM	2 x RS-232 / 422 / 485 ( Adjustable through BIOS )
Audio	1x Audio_out & Mic_in
Wireless Network	Optional (WiFi / Bluetooth / 4G / 5G )
Expansion	
M.2	1*M.2 ( Key-E, 2230, PCIe+USB, Wifi+BT )
	1*M.2 ( Key-B, 3042/3052, PCIe/ USB 3.0+USB2.0, 4G/5G )
	1*M.2 ( Key-M, 2280, SATA / SSD )
SIM Socket	1x SIM Socket
Display	
LCD Size	13.3" ( 16:9 )
Resolution	1920 x 1080 ( FHD )
Brightness (cd/m <sup>2</sup> )	400 cd/m <sup>2</sup>
Contrast Ratio	900:1
Backlight MTBF	50000 hrs
Viewing Angle	85 / 85 / 85 / 85 (CR≥10) ( L / R / U / D )
Touch screen	
Touch Type	10 point PCAP
Surface Hardness	≥7H

Power	
Power Adapter	1 x Optional AC/DC 12V/5A , 60W
Power Mode	Support AT, ATX Mode
Power Input	2-Pin Terminal Block Connector with Power Input 9~36VDC
Power Protection	OVP (Over Voltage Protection)   OCP (Over Current Protection)   RPP (Reverse Polarity Protection)
Power Consumption	≤35W
Physical	
Material	Aluminum alloy panel, anodized treatment
Mounting	Stand / Wall / VESA / Panel
Dimension (W x H x D)	345 x 216 x 60 mm
Cut-out Size	331 x 202 mm
Packing Size	450 x 170 x 350 mm
Weight (Net)	2.8 KG
Environment	
Operating Temperature	-20~70°C ( -4~158°F )
Storage Temperature	-30~80°C (-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Protection	1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
IP Level	Front Panel IP66
EMC	CE, FCC, UL, KC, Class A, ROHS , IEC / EN 62368-1

### Dimension & I/O

The technical drawings show the following dimensions and I/O definitions:

- Front View:** Overall width 344.50 mm, height 216.00 mm. The display area is 13.3" (FHD).
- Side View:** Total thickness 60.00 mm, with a mounting flange height of 7.00 mm.
- Cutout View:** Shows the internal layout of ports with a width of 100.00 mm and a height of 100.00 mm.
- I/O Definition:**
  - A: DC 9V~36V
  - B: COM1:RS-232 / 422 / 485
  - C: COM2:RS-232/422/485
  - D: 2 x LAN
  - E: H-DMI
  - F: 2 x USB 3.0
  - G: 1 x LAN
  - H: 2 x USB 3.0
  - I: Audio
  - J: Power Button

**Panel Cutout Dimensions: 331 x 202 mm (13.03 x 7.95 in )**

### Ordering info

Available models	Description
PPC-C133WAC	13.3" Fanless Industrial Panel PC Intel® Elkhart Lake Celeron J6412 2.0GHz Processor With Capcice touch
PPC-X133WAC	13.3" Fanless Industrial Panel PC Intel® Elkhart Lake Atom X6425E 2.0GHz Processor With Capcice touch

### Packing list

1 x Standard product
1 x 60W PSU (Power Supply)
1 x Power cable & plug
8 x Panel mount metal clips